TEFCOLD®

Bakery and Supermarket

TEFCOLD®

BAKERY
supermarket

Products for storage and display of food, pastry etc. for bakeries and supermarkets, all produced according to the Tefcold quality demands.

The SUPER-B Series is a very flexible plug-in alternative to remote operated installations.

The UHD200 with 2 thermostats can be used as both chiller and freezer according to your customers needs.

» Bakery

Othello 100

- LED light for better display
- Black exterior
- Heated curved glass
- Ventilated cooling
- Self closing sliding doors
- 3 Glass shelves included
- Digital thermostat
- Easy clean interior
- Adjustable feet

UPD200

- Double glass on four sides
- 5 adjustable wire shelves
- Internal LED light
- Aluminium finish
- Ventilated cooling
- Automatic defrost
- Digital thermostat
- Easy clean interior
- Lockable castors

Technical specifications

Model	OTHELLO 100	UPD200
Climate Class	N	N
Temperature Range, °C	1 to 8	2 to 12
Gross Volume, l	-	468
Net Volume, l	-	425
External Dimensions, WxDxH	1000x740x1276	706x706x1800
Internal Dimensions, WxDxH	-	638x632x1180
Doors	2 sliging glass	1 glass
Shelves/Baskets	3 glass	5 wire
Outer Body	Powder coated / SS304	Aluminium
Interior	SS304	Glass / SS304 bottom
Castors/Feet	4 adjustable feet	4 wheels
Lock	N	N
Voltage/Frequency, V/Hz	220-240/50	220-240/50
Input Power, W	497	350
Energy Consumption, kWh/24h	See www.tefcold.dk	See www.tefcold.dk
Gross Weight, kg	285	170
Net Weight, kg	200	160
Noise Level dbA	42	46
Type of Cooling	Ventilated	Ventilated
Type of Defrost	Automatic	Automatic
Controller	Digital	Digital
Thermometer	Y	Y
Refrigerant	R134a	R134a
Charge, g	-	260
Internal Light	LED	LED

ECO-friendly

» Bakery

UPD80 Black

- Double glass on four sides
- 3 adjustable shelves
- Hinged glass door
- Internal LED light
- Black finish
- Ventilated cooling
- Automatic defrost

UPD60 Black

- Double glass on four sides
- 2 adjustable shelves
- Hinged glass door
- Internal LED light
- Black finish
- Ventilated cooling
- Automatic defrost

UPD80 Grey

- Double glass on four sides
- 3 adjustable shelves
- Hinged glass door
- Internal LED light
- Grey finish
- Ventilated cooling
- Automatic defrost

Technical specifications

Model	UPD60 Grey	UPD80 Grey	UPD60 Black	UPD80 Black
Climate Class	N	N	N	N
Temperature Range, °C	2 to 12	2 to 12	2 to 12	2 to 12
Gross Volume, l	60	80	60	80
Net Volume, l	58	78	58	78
External Dimensions, WxDxH	428x386x855	428x386x1000	428x386x855	428x386x1000
Internal Dimensions, WxDxH	400x346x460	400x346x610	400x346x460	400x346x610
Doors	1 glass	1 glass	1 glass	1 glass
Shelves/Baskets	2	3	2	3
Outer Body	Grey finish, ABS	Grey finish, ABS	Black finish, ABS	Black finish, ABS
Interior	Grey finish, ABS	Grey finish, ABS	Black finish, ABS	Black finish, ABS
Castors/Feet	4 feet	4 feet	4 feet	4 feet
Lock	N	N	N	N
Voltage/Frequency, V/Hz	220-240/50	220-240/50	220-240/50	220-240/50
Input Power, W	164	164	164	164
Energy Consumption, kWh/24h	See www.tefcold.dk	See www.tefcold.dk	See www.tefcold.dk	See www.tefcold.dk
Gross Weight, kg	32	39	32	39
Net Weight, kg	30	36	30	36
Noise Level dbA	42	42	42	42
Type of Cooling	Ventilated	Ventilated	Ventilated	Ventilated
Type of Defrost	Automatic	Automatic	Automatic	Automatic
Controller	Electronic	Electronic	Electronic	Electronic
Thermometer	Y	Y	Y	Y
Refrigerant	R134a	R134a	R134a	R134a
Charge, g	100	120	100	120
Internal Light	LED	LED	LED	LED
Option: Charged with R600a	✓	✓	✓	✓

» Supermarket

SUPER-B45C Desk Cooler for Island installation (Bumper bars as option)

- Sliding curved glass lids for easy access to products
- Adjustable dividers
- Adjustable shelves
- Adjustable legs
- Fan assisted cooling
- Electronic controller

False bottom for air circulation

Adjustable dividers/shelves

Fresh meat version available, 0 to +2 °C

SUPER-B210C Desk Cooler

- Sliding curved glass lids for easy access to products
- Adjustable dividers
- Adjustable shelves
- Adjustable legs
- Fan assisted cooling
- Electronic controller

Technical specifications

Model	SUPER-B45C	SUPER-B185C	SUPER-B210C	SUPER-B250C
Climate Class	N	N	N	N
Temperature Range, °C	2 to 10	2 to 10	2 to 10	2 to 10
Gross Volume, l	666	789	912	1109
Net Volume, l	468	550	641	786
External Dimensions, WxDxH	1856x858x815	1856x858x890	2106x858x890	2506x858x890
Internal Dimensions, WxDxH	1720x720x525	1720x720x602	1970x720x602	2370x720x602
Doors	2 curved sliding glass lids	2 curved sliding glass lids	2 curved sliding glass lids	2 curved sliding glass lids
Shelves/Dividers	4/3	4/3	5/4	6/5
Outer Body	White	White	White	White
Interior	Stucco aluminium	Stucco aluminium	Stucco aluminium	Stucco aluminium
Castors/Feet	6 legs, wheels as option	6 legs, wheels as option	6 legs, wheels as option	6 legs, wheels as option
Lock	N	N	N	N
Voltage/Frequency, V/Hz	220-240/50	220-240/50	220-240/50	220-240/50
Input Power, W	570	570	680	680
Energy Consumption, kWh/24h	See www.tefcold.dk	See www.tefcold.dk	See www.tefcold.dk	See www.tefcold.dk
Gross Weight, kg	147	160	193	219
Net Weight, kg	132	144	175	200
Noise Level dbA	53	53	53	53
Type of Cooling	Fan assisted	Fan assisted	Fan assisted	Fan assisted
Type of Defrost	Automatic	Automatic	Automatic	Automatic
Controller	Electronic	Electronic	Electronic	Electronic
Thermometer	Digital	Digital	Digital	Digital
Refrigerant	R404a	R404a	R404a	R404a
Charge, g	200	200	250	250
Internal Light	LED as option	LED as option	LED as option	LED as option
Option: Charged with R290	✓	✓	✓	✓

» Supermarket

SUPER-B185F Desk Freezer

- Sliding curved glass lids for easy access to products
- Adjustable legs
- Electronic controller

SUPER-B250F Desk Freezer

- Sliding curved glass lids for easy access to products
- Adjustable legs
- Electronic controller



Heated frame with smooth sliding lids

Moveable dividers

Technical specifications

Model	SUPER-B45F	SUPER-B185F	SUPER-B210F	SUPER-B250F
Climate Class	N	N	N	N
Temperature Range, °C	-18 to -24	-18 to -24	-18 to -24	-18 to -24
Gross Volume, l	666	789	912	1109
Net Volume, l	470	563	655	797
External Dimensions, WxDxH	1856x858x815	1856x858x890	2106x858x890	2506x858x890
Internal Dimensions, WxDxH	1720x720x525	1720x720x602	1970x720x602	2370x720x602
Doors	2 curved sliding glass lids	2 curved sliding glass lids	2 curved sliding glass lids	2 curved sliding glass lids
Shelves/Dividers	2	3	3	4
Outer Body	White	White	White	White
Interior	Stucco aluminium	Stucco aluminium	Stucco aluminium	Stucco aluminium
Castors/Feet	6 legs, wheels as option	6 legs, wheels as option	6 legs, wheels as option	6 legs, wheels as option
Lock	N	N	N	N
Voltage/Frequency, V/Hz	220-240/50	220-240/50	220-240/50	220-240/50
Input Power, W	570	500	620	620
Energy Consumption, kWh/24h	See www.tefcold.dk	See www.tefcold.dk	See www.tefcold.dk	See www.tefcold.dk
Gross Weight, kg	126	138	170	191
Net Weight, kg	111	122	152	172
Noise Level dbA	53	53	53	53
Type of Cooling	Fan assisted	Fan assisted	Fan assisted	Fan assisted
Type of Defrost	Automatic	Automatic	Automatic	Automatic
Controller	Electronic	Electronic	Electronic	Electronic
Thermometer	Digital	Digital	Digital	Digital
Refrigerant	R404a	R404a	R404a	R404a
Charge, g	200	200	250	250
Internal Light	LED as option	LED as option	LED as option	LED as option
Option: Charged with R290	✓	✓	✓	✓

» Supermarket

Accessories SUPER-B Series

Bumper Bars and Socket

- Bumper bars for stand-alone and as kit for back-to-back installation
- Socket with diffuser for air-intake as kit

Back-to-Back Brackets

- Brackets for stable back-to-back installation

Internal Light

- LED light for low energy consumption

Back-to-Back Ventilation

- Easy to fit ventilation covers for back-to-back installations

» Supermarket

UHD200

- Open top for easy access to products
- Internal horizontal light on two sides
- Glass sides for better presentation of products
- Ventilated cooling
- 2 bumper bars for protection of cabinet
- Wheels
- Thermometer
- Option: Night curtain



Adjustable shelves



Night curtain as option

2 thermostats for switching between cooler or freezer

UHD200-2

- 2 thermostats for switching from cooler to freezer
- Open top for easy access to products
- Internal horizontal light on two sides
- Glass sides for better presentation of products
- Ventilated cooling
- 2 bumper bars for protection of cabinet
- Wheels
- Thermometer
- Option: Night curtain

Technical specifications

Model	UHD200	UHD200/2 THERMO
Climate Class	N	N
Temperature Range, °C	-2 to 5/-12 to -24	-2 to 5/-12 to -24
Gross Volume, l	200	200
Net Volume, l	165	165
External Dimensions, WxDxH	1010x1260x900	1010x1260x900
Internal Dimensions, WxDxH	705x1070x490	705x1070x490
Doors	Curtain as option	Curtain as option
Shelves/Baskets	3, wire	3, wire
Outer Body	RAL7031	RAL7031
Interior	Coated steel	Coated steel
Castors/Feet	4 wheels	4 wheels
Lock	N	N
Voltage/Frequency, V/Hz	220-240/50	220-240/50
Input Power, W	850	850
Energy Consumption, kWh/24h	See www.tefcold.dk	See www.tefcold.dk
Gross Weight, kg	142	142
Net Weight, kg	132	132
Noise Level dbA	49	49
Type of Cooling	Ventilated	Ventilated
Type of Defrost	Automatic	Automatic
Controller	Digital	Digital
Thermometer	Y	Y
Refrigerant	R404a	R404a
Charge, g	600	600
Internal Light	2x30W Neon	2x30W Neon
Canopy Light	N	N